

THERMOMETER

PCE-LTD 100



- » **USB data logger for dry ice**
- » **Data export directly as PDF**
- » **Waterproof housing IP67**
- » **Robust metal housing**
- » **For temperatures between -80 ... +70 °C / -112 ... +158 °F**
- » **Instantly replaceable battery**

The thermometer has a measuring range of -80... +70 °C. This makes the thermometer suitable for measuring tasks at particularly low temperatures. With the integrated measured value memory for 17280 measured data and the battery, the thermometer can carry out measurements independently and output them to a PC for later analysis. Thanks to its compact design and its metal housing with IP67 protection class, the thermometer can be integrated, for example, during the transport of medical products or other frozen products. This allows the cold chain to be monitored with the thermometer.

In order to read out the measurement data, the thermometer must be connected to a PC. From there, the thermometer is recognized as a mass data storage device. The software can now read out the thermometer in order to analyze the measurement data. The measurement data recorded by the thermometer can be exported as XLS, CSV, PDF, TXT and CIN for further processing. The graphic can also be exported as a JPG. At the same time, the thermometer can be set via the software. Among other things, the operator sets the start time, storage interval, the unit and the alarm limits. The thermometer can also be set so that it automatically outputs an exported file of the measurement data. The file formats PDF, DLG, CSV, XLS and TXT are available for selection. This has the particular advantage that the measurement data can be imported directly into a data management system.

Specification

Temperature	
Measuring range	-80 ... +30 °C
Resolution	0,1 °C
Accuracy	±1 °C
Temperature	
Measuring range	-31 ... +70 °C
Resolution	0,1 °C
Accuracy	±0.5 °C

General technical data	
Storage medium	USB pen drive
Storage capacity	17280 Values
Storage interval from	1 s
Storage interval to	24 h
Operating time	2 Year(s)
Operating time additional information	2 years @ 25°C / 15 min storage interval 30 days @ -80 ... -70°C / 15 min storage interval
file format	TXT, CSV, XLS, JPG, bmp, PDF, CIN
Protection class (device)	IP67
(Rechargeable) battery	1 x 3,6 V 2/3 AA (ER14335) , lithium
Capacity	1650 mAh
Operating conditions	-80 ... 70 °C , 0 ... 95 % RH
Storage conditions	-40 ... 70 °C , 0 ... 95 % RH
Dimensions (L x W x H)	115 x 18 x 18 mm
Weight	95 g